**International Product Assurance** LABORATORIES

## Testing **Checklist**

**ANSI** A137.3 **2CM Gauged Porcelain Pavers** 

6555

CRFDITFI

ÆII

CONTRACTOR .

International Product Assurance Laboratories (formerly FICNA Product Performance Testing Laboratory) offers the full scope of testing to meet the requirements specified in A137.3:

CAUTIO

HOT

Hicobiological testing also available

Tests to determine the antimitotial

- Gauged Porcelain Pavers 2CM thick (Table 6)
- ASTM C499, C485, C502 Facial and thickness dimensions, warpage, and wedging
- ANSI A137.3, Section 8.6 Soft Body Impact (Over sand bed and/or pedestals)
- ANSI A137.3, Section 8.7 Hard Body Impact (Over sand bed and/or pedestals)
- ASTM C1505 Breaking Strength/Modulus of Rupture
- ANSI A137.3, Section 5.3.11 Compressive Strength
- ANSI A137.3, Section 8.5 Dry Bond Strength
- ANSI A137.3, Section 8.5 Wet Bond Strength (Back-layered only)
- ASTM C373 Water Absorption
- ANSI A137.3, Section 5.3.1.2.2 Back-Layer Saturation (Back-layered only)
- ASTM C1378 Stain Resistance
- ASTM C650 Chemical Resistance
- ANSI A326.3 DCOF (Tiles intended for floor applications)
- ASTM C609 Color Uniformity (V0 tiles only)
- ASTM C424 Crazing Resistance (Glazed tile only)
- ASTM C484 Thermal Shock Resistance
- ASTM C372 Thermal Expansion (Tile panels/slabs only)
- ASTM C1026 Resistance to Freeze/Thaw Cycling (Tiles intended for freeze/thaw conditions)
- ASTM C1243 Abrasion Resistance

## Additional considerations

- Additional testing may be needed for characterizing the slip resistance of the tile surface, such as German ramp testing to DIN 16165 (formerly DIN 51130).
- ISO methods available for compliance with international specifications.
- Place a testing order at www.TCNAtile.com or contact us to discuss your custom testing needs.
- testing@IPALaboratories.com 855-IPA-LABS